

Datum: 09.05.2025



(slika je simbolična)

[krog. ventil med., pnevm. vklop vzmetno odpiranje, 1 1/4](#)

Kategorija: [Brass ball valve, single-acting actuator](#)

Šifra: **103544RIE**

Kratek opis

2-way brass ball valve, Pneumat. actuation drive spring opening, Operating temp. max. 70 °C, Rp 1 1/4, DN 32, PN max. 40 bar

2-way cock, full bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 1 1/4
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	single-acting - spring to open
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
D [mm]	30.0
DN	32
PN [bar]	40
a/f [mm]	50
Max. delovna temperatura [°C]	70
Kot vrtenja [°]	90
L [mm]	110.0
A [mm]	137.0
B [mm]	173.0