

Datum: 09.05.2025



(slika je simbolična)

## [krog. ventil med., pnevm. vklop vzmetno odpiranje, 2 1/2](#)

Kategorija: [Brass ball valve, single-acting actuator](#)

Šifra: **103547RIE**

### Kratek opis

2-way brass ball valve, Pneumat. actuation drive spring opening, Operating temp. max. 70 °C, Rp 2 1/2, DN 65, PN max. 25 bar

2-way cock, full bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

### Tehnične Specifikacije

|                                   |                                            |
|-----------------------------------|--------------------------------------------|
| Min. delovna temperatura [°C]     | -20                                        |
| Adapter ventila                   | Supplied as standard                       |
| Material krogelnega ventila       | Nickel-plated brass, with ISO flange plate |
| Navoj                             | Rp 2 1/2                                   |
| Pogonski material                 | Anodised aluminium                         |
| Premaz za krogelni ventil         | PTFE / FKM                                 |
| Premaz za pogon                   | NBR                                        |
| Različica                         | single-acting - spring to open             |
| Priporočeni vodeni tlak [bar]     | 5.5                                        |
| Max. vodeni tlak aktuatorja [bar] | 10                                         |
| PN [bar]                          | 25                                         |
| D [mm]                            | 57.0                                       |
| DN                                | 65                                         |
| Max. delovna temperatura [°C]     | 70                                         |
| a/f [mm]                          | 83                                         |
| Kot vrtenja [°]                   | 90                                         |
| L [mm]                            | 155.0                                      |
| A [mm]                            | 209.0                                      |
| B [mm]                            | 230.0                                      |