

Datum: 11.05.2025



(slika je simbolična)

krog. ventil robustnejša oblika, Z ročico, ročni, ET/ET, R 1 1/2

Kategorija: [Ball valve with hand lever, ET/ET](#)

Šifra: **103285RIE**

Kratek opis

Ball valve heavy duty design, Manual lever, ET/ET, nickel-plated brass, Operating temp. -20 °C to 130 °C, R 1 1/2, PN max. 100 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	R 1 1/2
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	R thread acc. to DIN EN 10226 (ISO 7-1)
Stebelno tesnilo	PTFE
E [mm]	21.2
F [mm]	21.2
DN	40
a/f [mm]	57
PN [bar]	100
B [mm]	102.9
Max. delovna temperatura [°C]	130
L [mm]	136.0
A [mm]	150.0