

Datum: 30.04.2025



(slika je simbolična)

## Krog. ventil robustnejša oblika, z ročico, ročni, IT/ET, G/R 1 1/4

Kategorija: [Ball valve with hand lever, IT/ET](#)  
Šifra: **103276RIE**

### Kratek opis

Ball valve heavy duty design, Manual lever, IT/ET, nickel-plated brass, Operating temp. -20°C to 130°C, G/R 1 1/4, PN max. 80 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

### Tehnične Specifikacije

|                               |                                                            |
|-------------------------------|------------------------------------------------------------|
| Min. delovna temperatura [°C] | -20                                                        |
| Krogelno tesnilo              | PTFE                                                       |
| Krogla                        | Chrome-plated brass                                        |
| Material navojev              | Brass with a bare metal surface                            |
| Navoj                         | G/R 1 1/4                                                  |
| Ohišje                        | Nickel-plated brass                                        |
| Ročica                        | Aluminium, painted black                                   |
| Standardni navoj              | G thread DIN EN ISO 228-1, R thread DIN EN 10226 (ISO 7-1) |
| Stebelno tesnilo              | PTFE                                                       |
| F [mm]                        | 16.0                                                       |
| E [mm]                        | 21.2                                                       |
| DN                            | 32                                                         |
| a/f 1 [mm]                    | 49                                                         |
| a/f 2 [mm]                    | 50                                                         |
| PN [bar]                      | 80                                                         |
| B [mm]                        | 95.0                                                       |
| L [mm]                        | 100.0                                                      |
| Max. delovna temperatura [°C] | 130                                                        |
| A [mm]                        | 150.0                                                      |