

Datum: 01.05.2025



(slika je simbolična)

krog. ventil robustnejša oblika, Z ročico, ročni, IT/ET, G/R 1/4

Kategorija: [Ball valve with hand lever, IT/ET](#)

Šifra: **103271RIE**

Kratek opis

Ball valve heavy duty design, Manual lever, IT/ET, nickel-plated brass, Operating temp. -20 °C to 130 °C, G/R 1/4, PN max. 80 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	G/R 1/4
Ohišje	Nickel-plated brass
Ročica	Aluminium, painted black
Standardni navoj	G thread DIN EN ISO 228-1, R thread DIN EN 10226 (ISO 7-1)
Stebelno tesnilo	PTFE
F [mm]	7.0
DN	8
E [mm]	11.0
a/f 1 [mm]	18
a/f 2 [mm]	18
L [mm]	49.0
B [mm]	51.5
A [mm]	75.0
PN [bar]	80
Max. delovna temperatura [°C]	130