

Datum: 12.05.2025



(slika je simbolična)

## Krog. ventil za vodo,z ročico, ročni, IT/IT, G 1/2, DN 15

Kategorija: [Potable water ball valves](#)

Šifra: **133163RIE**

### Kratek opis

Potable water ball valve, Nickel-plated brass, Manual lever, IT/IT, G 1/2, DN 15, Operating temp. -15 °C to 110 °C, PN max. 40 bar

Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

### Tehnične Specifikacije

|                               |                                               |
|-------------------------------|-----------------------------------------------|
| Min. delovna temperatura [°C] | -15                                           |
| Aplikacije                    | Potable water, water                          |
| DVGW odobritev                | DIN EN 13828:2003-12, DVGW W 570              |
| Krogelno tesnilo              | PTFE                                          |
| Krogla                        | Chrome-plated brass                           |
| Material navojev              | Brass                                         |
| Navoj                         | G 1/2                                         |
| Ohišje                        | Nickel-plated brass (outside), brass (inside) |
| Ročica                        | Aluminium                                     |
| Standardni navoj              | Thread acc. to DIN EN ISO 228-1               |
| Stebelno tesnilo              | PTFE / EPDM / HNBR                            |
| DN                            | 15                                            |
| PN [bar]                      | 40                                            |
| B [mm]                        | 45.8                                          |
| L [mm]                        | 50.0                                          |
| A [mm]                        | 85.0                                          |
| Max. delovna temperatura [°C] | 110                                           |