

Datum: 01.05.2025



(slika je simbolična)

## Krogelni ventil 3/2 »FUTURA«, zaklepni, Velikost 1, G 1/4

Kategorija: [Ball valves](#)

Šifra: **100283RIE**

### Kratek opis

Ball valve 3/2-way »FUTURA«, lockable, Size 1, G 1/4,  
Exhaust G 1/4, Input pressure max. 16 bar, Temperature -10  
°C to 50 °C

Lockable ball valve, 3/2-way type including silencer,  
mechanically operated.

Rotary switch can be turned 90°, with indication of  
positions:

Horizontal: Input closed - outlet exhausted

Vertical: Flow open - exhaust closed

Exhaust air can be collected.

### Tehnične Specifikacije

|                                   |                                                                      |
|-----------------------------------|----------------------------------------------------------------------|
| Min. temperaturno območje<br>[°C] | -10                                                                  |
| Izpušni zrak                      | G 1/4<br>At $P_2 = 6$ bar and<br>pressure drop $\Delta p = 1$<br>bar |
| Merjenje pretoka                  |                                                                      |
| Navoj                             | G 1/4                                                                |
| Ohišje                            | PA66 GF60                                                            |
| Priključni navoj                  | Material: Die-cast zinc                                              |
| Serijska                          | FUTURA                                                               |
| Srednje                           | Compressed air,<br>neutral gases                                     |
| Velikost                          | 1                                                                    |
| Max. vhodni tlak [bar]            | 16                                                                   |
| Max. temperaturno<br>območje [°C] | 50                                                                   |
| A [mm]                            | 52.0                                                                 |
| C [mm]                            | 54.5                                                                 |
| B [mm]                            | 87.5                                                                 |
| Pretok [l/min]                    | 1900                                                                 |