

Datum: 06.05.2025



(slika je simbolična)

krogelni ventil EN 331, DVGW, metuljasta ročica, IT/IT, Rp 3/8

Kategorija: [Ball valve with butterfly handle, DIN DVGW, IT/IT](#)
Šifra: **133188RIE**

Kratek opis

Ball valve EN 331, DVGW, nickel-plated brass, Butterfly handle, IT/IT, Rp 3/8, DN 10, Operat. temp. -15 °C to 60 °C, PN max. 5 bar

Ball valves with full bore, for gas installations. Applications: Natural gas, LPG, town gas

Tehnične Specifikacije

Delovna temperatura	-15 °C to 60 °C for gas
Delovni tlak	max. 5 bar (pressure class MOP 5 acc. to DIN EN 331)
DVGW odobritev	DIN EN 331:2013-05
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass
Navoj	Rp 3/8
Ohišje	Nickel-plated brass
Ročica - metuljček	Aluminium
Standardni navoj	Thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / EPDM / HNBR
DN	10
B [mm]	30.6
A [mm]	47.0
L [mm]	48.6