

Datum: 01.05.2025



(slika je simbolična)

## [krogelni ventil fina nastavitvev, nikljana lahka medenina, Rp 1/2](#)

Kategorija: [Potable water ball valves with fine adjustment](#)

Šifra: **138873RIE**

### Kratek opis

Ball valve fine adjustment, Potable water suitable, nickel-plated bright brass, Temp. -15°C to 120°C, Rp 1/2, DN 15, PN max 50 bar

Brass ball valves in the standard series with fine adjustment.

Unlike our classic standard ball valves (open-close function), this model features a special stem technology that allows finely modulated opening and closing of the line.

The flow rate can be regulated extremely precisely as a result.

The cock is made of low-lead brass with a bare brass surface on the inside. It is thus safe to use with drinking water. This valve complies with the European standard EN 13828 and the working paper DVGW W 570.

### Tehnične Specifikacije

|                               |                                                                         |
|-------------------------------|-------------------------------------------------------------------------|
| Min. delovna temperatura [°C] | -15                                                                     |
| DVGW odobritev                | DIN EN 13828:2003-12, DVGW W 570                                        |
| Kolo                          | Plastic                                                                 |
| Krogelno tesnilo              | PTFE                                                                    |
| Krogla                        | Chrome-plated brass                                                     |
| Material navojev              | Brass with a bare metal surface                                         |
| Navoj                         | Rp 1/2                                                                  |
| Ohišje                        | Nickel-plated brass (outside), brass with a bare metal surface (inside) |
| Standardni navoj              | Thread acc. to ISO 7/1                                                  |
| Stebelno tesnilo              | PTFE / NBR                                                              |
| DN                            | 15                                                                      |
| PN [bar]                      | 50                                                                      |
| L [mm]                        | 61.1                                                                    |
| B [mm]                        | 70.7                                                                    |
| A [mm]                        | 83.2                                                                    |
| Max. delovna temperatura [°C] | 120                                                                     |