

Datum: 09.05.2025



(slika je simbolična)

krogelni ventil medenina, pnevmatski vklop duple-acting, Rp 1 1/2

Kategorija: [Brass ball valve, double-acting actuator](#)

Šifra: **103569RIE**

Kratek opis

Brass ball valve, Pneumat. actuation drive, double-acting,
Operating temperature -20°C to 150°C, Rp 1 1/2, DN 40, PN
max. 16 bar

Ball valves with pneumatic actuator.

Pneumatic, double-piston, part-turn actuator, double-rocker
principle.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperaturno območje [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 1 1/2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Max. vodeni tlak [bar]	5.6
Max. obratovalni tlak [bar]	16
DN	40
Max. temperaturno območje [°C]	80
Kot vrtenja [°]	90
A [mm]	114.0
L [mm]	114.0
B [mm]	129.0
Max. delovna temperatura [°C]	150