

Datum: 10.05.2025



(slika je simbolična)

## krogelni ventil medenina, pnevmatski vklop duple-acting, Rp 1 1/4

Kategorija: [Brass ball valve, double-acting actuator](#)

Šifra: **158800RIE**

### Kratek opis

Brass ball valve, Pneumat. actuation drive, NAMUR, double-acting, Operating temp. -20°C to 150°C, Rp 1 1/4, DN 32, PN max. 16 bar

Ball valves with pneumatic actuator.

Pneumatic, double-piston, part-turn actuator, double-rocker principle.

### Tehnične Specifikacije

|                                            |                                                 |
|--------------------------------------------|-------------------------------------------------|
| Min. delovna temperatura aktuatorja [°C]   | -20                                             |
| Min. delovni tlak krogelnega ventila [°C]  | -20                                             |
| Adapter ventila                            | Integrated to NAMUR                             |
| Material krogelnega ventila                | Nickel-plated brass, with flange plate ISO 5211 |
| Navoj                                      | Rp 1 1/4                                        |
| Pogonski material                          | Anodised aluminium                              |
| Premaz za krogelni ventil                  | PTFE / FKM                                      |
| Premaz za pogon                            | NBR                                             |
| Različica                                  | double-acting                                   |
| Priporočeni vodeni tlak [bar]              | 5.6                                             |
| Max. vodeni tlak aktuatorja [bar]          | 8.4                                             |
| Max. delovni tlak krogelnega ventila [bar] | 16                                              |
| DN                                         | 32                                              |
| Max. delovna temperatura aktuatorja [°C]   | 80                                              |
| Kot vrtenja [°]                            | 90                                              |
| L [mm]                                     | 103.0                                           |
| B [mm]                                     | 122.8                                           |
| Max. delovni tlak krogelnega ventila [°C]  | 150                                             |
| A [mm]                                     | 159.0                                           |