

Datum: 01.05.2025



(slika je simbolična)

## krogelni ventil medenina, pnevmatski vklop enojno delovanje, Rp 2

Kategorija: [Brass ball valve, single-acting actuator](#)

Šifra: **158752RIE**

### Kratek opis

Brass ball valve, Pneumat. actuation drive, NAMUR, single-acting, Operating temp. -20 °C to 150 °C, Rp 2, DN 50, PN max. 16 bar

Ball valves with pneumatic actuator.

Pneumatic, double-piston, part-turn actuator, double-rocker principle.

### Tehnične Specifikacije

|                                            |                                                 |
|--------------------------------------------|-------------------------------------------------|
| Min. delovna temperatura aktuatorja [°C]   | -20                                             |
| Min. delovni tlak krogelnega ventila [°C]  | -20                                             |
| Adapter ventila                            | Integrated to NAMUR                             |
| Material krogelnega ventila                | Nickel-plated brass, with flange plate ISO 5211 |
| Navoj                                      | Rp 2                                            |
| Pogonski material                          | Anodised aluminium                              |
| Premaz za krogelni ventil                  | PTFE / FKM                                      |
| Premaz za pogon                            | NBR                                             |
| Različica                                  | single-acting - spring to close                 |
| Priporočeni vodeni tlak [bar]              | 5.6                                             |
| Max. vodeni tlak aktuatorja [bar]          | 8.4                                             |
| Max. delovni tlak krogelnega ventila [bar] | 16                                              |
| DN                                         | 50                                              |
| Max. delovna temperatura aktuatorja [°C]   | 80                                              |
| Kot vrtenja [°]                            | 90                                              |
| L [mm]                                     | 134.0                                           |
| Max. delovni tlak krogelnega ventila [°C]  | 150                                             |
| B [mm]                                     | 155.0                                           |
| A [mm]                                     | 258.8                                           |