

Datum: 08.05.2025



(slika je simbolična)

## krogelni ventil nerjavno jeklo, Pneumat. vklop, T-izpust T1

Kategorija: [Stainless steel ball valve, double-acting, T-bore](#)

Šifra: **103629RIE**

### Kratek opis

3-way stainless steel ball valve, Pneumat. actuation drive, T-hole T1, Operating temp. -20 °C to 70 °C, Rp 1 1/4, PN max. 63 bar

3-way cock, reduced bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Standardised interfaces:

Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.

Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.

Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

### Tehnične Specifikacije

|                                   |                                              |
|-----------------------------------|----------------------------------------------|
| Min. delovna temperatura [°C]     | -20                                          |
| Adapter ventila                   | Acc. to NAMUR<br>Stainless steel             |
| Material krogelnega ventila       | 1.4401, with ISO<br>flange plate<br>Rp 1 1/4 |
| Navoj                             | Anodised aluminium                           |
| Pogonski material                 | T 1                                          |
| Položaj                           | PTFE / FKM                                   |
| Premaz za krogelni ventil         | NBR                                          |
| Premaz za pogon                   | double-acting                                |
| Različica                         | 5.5                                          |
| Priporočeni vodeni tlak [bar]     | 10                                           |
| Max. vodeni tlak aktuatorja [bar] | 32                                           |
| DN                                | 36.5                                         |
| D [mm]                            | 50                                           |
| a/f [mm]                          | 63                                           |
| Max. obratovalni tlak [bar]       | 70                                           |
| Max. delovna temperatura [°C]     | 90                                           |
| Kot vrtenja [°]                   | 90.0                                         |
| L [mm]                            | 133.0                                        |
| A [mm]                            | 153.5                                        |
| B [mm]                            |                                              |