

Datum: 01.05.2025



(slika je simbolična)

## krogelni ventil nerjavno jeklo, Pneumat. vklop, T-izpust T2

Kategorija: [Stainless steel ball valve, double-acting, T-bore](#)Šifra: **103636RIE**

### Kratek opis

3-way stainless steel ball valve, Pneumat. actuation drive, T-hole T2, Operating temp. -20 °C to 70 °C, Rp 1 1/2, PN max. 63 bar

3-way cock, reduced bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Standardised interfaces:

Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.

Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.

Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

### Tehnične Specifikacije

|                                   |                                               |
|-----------------------------------|-----------------------------------------------|
| Min. delovna temperatura [°C]     | -20                                           |
| Adapter ventila                   | Acc. to NAMUR                                 |
| Material krogelnega ventila       | Stainless steel 1.4401, with ISO flange plate |
| Navoj                             | Rp 1 1/2                                      |
| Pogonski material                 | Anodised aluminium                            |
| Položaj                           | T 2                                           |
| Premaz za krogelni ventil         | PTFE / FKM                                    |
| Premaz za pogon                   | NBR                                           |
| Različica                         | double-acting                                 |
| Priporočeni vodeni tlak [bar]     | 5.5                                           |
| Max. vodeni tlak aktuatorja [bar] | 10                                            |
| D [mm]                            | 37.0                                          |
| DN                                | 40                                            |
| a/f [mm]                          | 55                                            |
| Max. obratovalni tlak [bar]       | 63                                            |
| Max. delovna temperatura [°C]     | 70                                            |
| Kot vrtenja [°]                   | 90                                            |
| L [mm]                            | 105.0                                         |
| A [mm]                            | 137.0                                         |
| B [mm]                            | 173.0                                         |