

Datum: 01.05.2025



(slika je simbolična)

krogelni ventil nerjavno jeklo, Pneumat. vklop, T-izpust T2

Kategorija: [Stainless steel ball valve, double-acting, T-bore](#)Šifra: **103637RIE**

Kratek opis

3-way stainless steel ball valve, Pneumat. actuation drive, T-hole T2, Operating temp. -20°C to 70°C, Rp 2, DN 50, PN max. 63 bar

3-way cock, reduced bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Standardised interfaces:

Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.

Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.

Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Acc. to NAMUR Stainless steel
Material krogelnega ventila	1.4401, with ISO flange plate
Navoj	Rp 2
Pogonski material	Anodised aluminium
Položaj	T 2
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	double-acting
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
D [mm]	47.5
DN	50
Max. obratovalni tlak [bar]	63
Max. delovna temperatura [°C]	70
a/f [mm]	71
Kot vrtenja [°]	90
L [mm]	115.0
A [mm]	161.0
B [mm]	196.5