

Datum: 30.04.2025



(slika je simbolična)

krogelni ventil nerjavno jeklo, Pneumat. vklop, L-izpust

Kategorija: [Stainless steel ball valve, double-acting, L-bore](#)Šifra: **103615RIE**

Kratek opis

3-way stainless steel ball valve, Pneumat. actuation drive, L-hole, Operating temp. -20°C to 70°C, Rp 3/4, DN 20, PN max. 63 bar

3-way cock, reduced bore.

Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Standardised interfaces:

Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211.

Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.

Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Acc. to NAMUR Stainless steel
Material krogelnega ventila	1.4401, with ISO flange plate Rp 3/4
Navoj	Anodised aluminium L 2
Pogonski material	PTFE / FKM
Položaj	NBR
Premaz za krogelni ventil	double-acting
Premaz za pogon	5.5
Različica	10
Priporočeni vodeni tlak [bar]	20
Max. vodeni tlak aktuatorja [bar]	23.0
DN	32
D [mm]	63
a/f [mm]	70
Max. obratovalni tlak [bar]	80.0
Max. delovna temperatura [°C]	90
L [mm]	116.0
Kot vrtenja [°]	136.0
A [mm]	
B [mm]	