

Datum: 11.05.2025



(slika je simbolična)

## krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 1

Kategorija: [Stainless steel ball valve, single-acting actuator](#)

Šifra: **158763RIE**

### Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, single-acting, Operating temp. -20 °C to 150 °C, Rp 1, PN max. 100 bar

Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

### Tehnične Specifikacije

|                                           |                                              |
|-------------------------------------------|----------------------------------------------|
| Min. delovna temperatura aktuatorja [°C]  | -20                                          |
| Min. delovni tlak krogelnega ventila [°C] | -20                                          |
| Adapter ventila                           | Integrated to NAMUR                          |
| Material krogelnega ventila               | Stainless steel                              |
| Navoj                                     | 1.4401/1.4301/1.4310/1.4408, with ISO flange |
| Pogonski material                         | Rp 1                                         |
| Premaz za krogelni ventil                 | Anodised aluminium                           |
| Premaz za pogon                           | PTFE / FKM                                   |
| Različica                                 | NBR                                          |
| Priporočeni vodeni tlak [bar]             | single-acting - spring to close              |
| Max. vodeni tlak aktuatorja [bar]         | 5.6                                          |
| DN                                        | 8.4                                          |
| Max. delovna temperatura aktuatorja [°C]  | 25                                           |
| L [mm]                                    | 80                                           |
| Kot vrtenja [°]                           | 85.0                                         |
| PN [bar]                                  | 90                                           |
| Max. delovni tlak krogelnega ventila [°C] | 100                                          |
| B [mm]                                    | 150                                          |
| A [mm]                                    | 185.7                                        |
|                                           | 258.8                                        |