

Datum: 01.05.2025



(slika je simbolična)

## krogelni ventil nerjavno jeklo, pnevmatski vklop, Rp 2

Kategorija: [Stainless steel ball valve, single-acting actuator](#)

Šifra: **103594RIE**

### Kratek opis

Stainless steel ball valve, Pneumatic actuation drive, single-acting, Operating temp. -20 °C to 150 °C, Rp 2, PN max. 40 bar

Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

### Tehnične Specifikacije

|                                |                                              |
|--------------------------------|----------------------------------------------|
| Min. delovna temperatura [°C]  | -20                                          |
| Min. temperaturno območje [°C] | -20                                          |
| Adapter ventila                | Supplied as standard                         |
| Material                       | Stainless steel                              |
| krogelnega ventila             | 1.4401/1.4301/1.4310/1.4408, with ISO flange |
| Navoj                          | Rp 2                                         |
| Pogonski material              | Anodised aluminium                           |
| Premaz za krogelni ventil      | PTFE / FKM                                   |
| Premaz za pogon                | NBR                                          |
| Različica                      | single-acting - spring to close              |
| Max. vodeni tlak [bar]         | 5.6                                          |
| PN [bar]                       | 40                                           |
| DN                             | 50                                           |
| Max. temperaturno območje [°C] | 80                                           |
| Kot vrtenja [°]                | 90                                           |
| L [mm]                         | 125.0                                        |
| Max. delovna temperatura [°C]  | 150                                          |
| B [mm]                         | 234.0                                        |
| A [mm]                         | 357.0                                        |