

Datum: 11.05.2025



(slika je simbolična)

## krogelni ventil robustnejša oblika, Z ročico, ročni, ET/ET, R 2

Kategorija: [Ball valve with hand lever, ET/ET](#)  
Šifra: **103286RIE**

### Kratek opis

Ball valve heavy duty design, Manual lever, ET/ET, nickel-plated brass, Operating temp. -20 °C to 130 °C, R 2, PN max. 80 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

### Tehnične Specifikacije

|                               |                                         |
|-------------------------------|-----------------------------------------|
| Min. delovna temperatura [°C] | -20                                     |
| Krogelno tesnilo              | PTFE                                    |
| Krogla                        | Chrome-plated brass                     |
| Material navojev              | Brass with a bare metal surface         |
| Navoj                         | R 2                                     |
| Ohišje                        | Nickel-plated brass                     |
| Ročica                        | Aluminium, painted black                |
| Standardni navoj              | R thread acc. to DIN EN 10226 (ISO 7-1) |
| Stebelno tesnilo              | PTFE                                    |
| E [mm]                        | 25.0                                    |
| F [mm]                        | 25.0                                    |
| DN                            | 50                                      |
| a/f [mm]                      | 70                                      |
| PN [bar]                      | 80                                      |
| B [mm]                        | 117.8                                   |
| Max. delovna temperatura [°C] | 130                                     |
| L [mm]                        | 159.5                                   |
| A [mm]                        | 175.0                                   |