

Datum: 30.04.2025



(slika je simbolična)

## krogelni ventil, visoki tlak, lahka izvedba, M18x1.5

Kategorija: [High-pressure ball valve steel, lightweight series](#)

Šifra: **103501RIE**

### Kratek opis

Ball valve, High pressure design, Lightweight series, Steel,  
Operating temp. -10 °C to 100 °C, M18x1.5, DN 10, PN max.  
500 bar

For liquid and lubricating media.

Available versions:

- For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1.
- For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1.
- With female pipe thread acc. to DIN ISO 228-1 (BSP).

### Tehnične Specifikacije

|                               |                          |
|-------------------------------|--------------------------|
| Min. delovna temperatura [°C] | -10                      |
| Bore inball                   | Full bore                |
| Gred izbirnika                | Steel                    |
| Kontrolno kroglično tesnilo   | POM                      |
| Krogla                        | Hard-chrome plated steel |
| Navoj                         | M18x1.5                  |
| Ohišje                        | Steel                    |
| Tesnilo gredi izbirnika       | NBR                      |
| DN                            | 10                       |
| O.D. za cevi [mm]             | 12L                      |
| B [mm]                        | 68.0                     |
| L [mm]                        | 75.0                     |
| A [mm]                        | 100.0                    |
| Max. delovna temperatura [°C] | 100                      |
| Max. obratovalni tlak [bar]   | 500                      |