

Datum: 01.05.2025



(slika je simbolična)

krogelni ventil visoki tlak, lahka izvedba, M36x2

Kategorija: [High-pressure ball valve steel, lightweight series](#)

Šifra: **103505RIE**

Kratek opis

Ball valve, High pressure design, Lightweight series, Steel,
Operating temp. -10 °C to 100 °C, M36x2, DN 25, PN max.
420 bar

For liquid and lubricating media.

Available versions:

- For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1.
- For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1.
- With female pipe thread acc. to DIN ISO 228-1 (BSP).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Bore inball	Full bore
Gred izbirnika	Steel
Kontrolno kroglično tesnilo	POM
Krogla	Hard-chrome plated steel
Navoj	M36x2
Ohišje	Steel
Tesnilo gredi izbirnika	NBR
DN	25
O.D. za cevi [mm]	28L
Max. delovna temperatura [°C]	100
L [mm]	108.0
B [mm]	128.0
A [mm]	187.0
Max. obratovalni tlak [bar]	420