

Datum: 08.05.2025



(slika je simbolična)

## L-obročni del, na votli vijak G 1/4, za cev zunanji Ø 8 mm

Kategorija: [L-ring nipple](#)

Šifra: **108837RIE**

### Kratek opis

L-ring piece, for hollow screw G 1/4, for hose exterior Ø 8 mm, Working pressure -0.98 to 16 bar, Operating temp. -20 °C to 70 °C

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

|                               |                     |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20                 |
| Min. delovni tlak [bar]       | -0.98               |
| Material                      | Nickel-plated brass |
| Priporočena cev               | PA, PU              |
| Rokav                         | POM black           |
| Serijska                      | click-clock         |
| Vpenjalni obroč               | Stainless steel     |
| Za banjo vijak                | G 1/4               |
| Za cevi O.D. [mm]             | 8                   |
| Max. delovni tlak [bar]       | 16                  |
| L2 [mm]                       | 17.0                |
| L1 [mm]                       | 26.0                |
| Max. delovna temperatura [°C] | 70                  |