

Datum: 30.04.2025



(slika je simbolična)

## ManometerCrNi jeklena varnostna verzijaG1/2, 0 - 4 bar, Ø100

Kategorija: [Pressure gauges \(CrNi steel type / safety housing\)](#)

Šifra: **102464RIE**

### Kratek opis

Pressure gauge, CrNi steel, Safety design, Connection radial bottom, G 1/2, Goods class 1.0, Measurement range 0 - 4 bar, Ø 100

Bourdon-tube pressure gauge (safety housing), CrNi steel type, with solid baffle wall and blow-out (safety housing). Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere.

### Tehnične Specifikacije

|                                            |                        |
|--------------------------------------------|------------------------|
| Min. sobna temperatura [°C]                | -40                    |
| Min. temperatura medija [°C]               | -40                    |
| Material                                   | CrNi steel             |
| Material Prozessanschluss                  | CrNi steel             |
| Položaj povezave                           | radial on bottom       |
| Povezava                                   | G 1/2                  |
| Prednje steklo                             | Laminated safety glass |
| Spodnja/Zgornja meja območja               | Positive pressure      |
| Stopnja rasti na območju skale - bar [bar] | 0.1                    |
| Razred točnosti                            | 1.0                    |
| Merilno območje max. bar                   | 4                      |
| Max. sobna temperatura [°C]                | 60                     |
| Premer [mm]                                | 100                    |
| Max. temperatura medija [°C]               | 200                    |
| Vrsta                                      | 232.30                 |