

Datum: 01.05.2025



(slika je simbolična)

## Medprirobnični zaporni ventil, Pneum. vklop, DN 150

Kategorija: [Butterfly valve, with single-acting actuator](#)

Šifra: **103680RIE**

### Kratek opis

Intermediate flange blocking flap, Pneumat. actuation drive, single-acting, Operating temp. -15°C to 120°C, DN 150, PN max. 16 bar

Butterfly valves with pneumatic actuator. Pneumatic actuators, double- or single acting version.

For water/steam, seawater, salt water, ester, ketones, alkalis, caustic soda, sodium hydroxide.

Not recommended for hydrocarbons, oils or greases.

### Tehnične Specifikacije

|                               |                                                           |
|-------------------------------|-----------------------------------------------------------|
| Min. delovna temperatura [°C] | -15                                                       |
| Adapter ventila               | Supplied as standard, operated by a 3/2- or 5/2-way valve |
| Disc                          | Stainless steel                                           |
| Gred izbirnika                | CF8M/1.4404                                               |
| Ohišje                        | SS416                                                     |
| Pogonski material             | Grey cast iron GG25                                       |
| Premaz za pogon               | epoxy resin coated, RAL 5015 color                        |
| Različica                     | Anodised aluminium                                        |
| Tesnilo                       | NBR                                                       |
| Tesnilo gredi izbirnika       | single-acting - spring to close                           |
| Min. vodeni tlak [bar]        | EPDM                                                      |
| Max. vodeni tlak [bar]        | EPDM                                                      |
| Max. obratovalni tlak [bar]   | 5                                                         |
| B [mm]                        | 5.5                                                       |
| Kot vrtenja [°]               | 16                                                        |
| Max. delovna temperatura [°C] | 59.0                                                      |
| H1 [mm]                       | 90                                                        |
| DN                            | 120                                                       |
| L [mm]                        | 138.0                                                     |
| H2 [mm]                       | 150                                                       |
| H3 [mm]                       | 216.0                                                     |
|                               | 265.0                                                     |
|                               | 395.0                                                     |