

Datum: 04.05.2025



(slika je simbolična)

Microfilter with differential pressure gauge, 0.01 µm, G 3/4

Kategorija: [Microfilter with differential pressure gauge](#)Šifra: **199815RIE**

Kratek opis

Microfilter with differential pressure gauge, 0.01µm, G3/4, Input pressure 4-12 bar, medium/ambient temp. 1.5 to 80°C, autom. drain valve
Ideal for filtering out aerosols and solid impurities larger than 0.01 µm.
Micro-filters should always be used in conjunction with a pre-filter.

Tehnične Specifikacije

Element filtra	Borosilicate (with glass-fibre material and foam plastic) At $P_1 = 7$ bar and pressure drop $\Delta_p = 0.1$ bar
Merjenje pretoka	G 3/4
Navoj	Aluminium
Ohišje	Aluminium
Posoda filtra	0.01
Ločevanje delcev [µm]	0.01
Rang filtra [µm]	0.01
Vsebnost olja v ostanku [mg/m ³]	0.01
Min. sobna temperatura [°C]	1.5
Min. temperatura medija [°C]	1.5
Max. označeni razpon diferencialnega manometra [bar]	2
Min. vhodni tlak [bar]	4
Max. vhodni tlak [bar]	12
C [mm]	28.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
Učinkovitost [%]	99.99
A [mm]	104.0
D [mm]	399.0
Pretok [l/min]	3666