

Datum: 07.05.2025



(slika je simbolična)

MikroFilter brez diferenčnega manometra, 0.01 µm, G 3/8

Kategorija: [Microfilter without differential pressure gauge](#)

Šifra: **101569RIE**

Kratek opis

Microfilter without differential pressure gauge, 0.01 µm, G 3/8, Input pressure 4 - 12 bar, Medium / ambient temp. 5 °C to 60 °C

Ideal for filtering out aerosols and solid impurities larger than 0.01 µm.

Micro-filters should always be used in conjunction with a pre-filter.

Tehnične Specifikacije

Element filtra	Borosilicate (with glass-fibre material and foam plastic)
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta p = 1.5\%$
Navoj	G 3/8
Ohišje	Aluminium
Posoda filtra	Aluminium
Rang filtra [µm]	0.01
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	12
C [mm]	57.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	83.0
Učinkovitost [%]	99.9999
B2 [mm]	335.0
D [mm]	353.0
Pretok [l/min]	1300