

Datum: 30.04.2025



(slika je simbolična)

MikroFilter»FUTURA«PC zbir.0.01 µmVel.2,G 3/8Avt.

Kategorija: [Microfilter with polycarbonate bowl and bowl guard](#)
Šifra: **100183RIE**

Kratek opis

Microfilter »FUTURA«, PC container and protective cage, 0.01 µm, Size 2, G 3/8, 1.5 - 16 bar, Temp. -10°C to 50°C, Fully-automatic

Micro-filters in modern design for compliance with strict compressed air purity requirements.

Micro-filters are used to separate solid oil, water and solid impurities as small as 0.01 µm from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Borosilicate glass fibre
Ločevanje prahu	> 0.01 µm 99.999 %
Merjenje pretoka	At P ₂ = 6 bar and pressure drop Δ _p = 0.1 bar
Navoj	G 3/8
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Vsebnost olja v ostanku [mg/m ³]	< 0.01
Rang filtra [µm]	0.01
Min. vhodni tlak [bar]	1.5
Velikost	2
Max. vhodni tlak [bar]	16
C [mm]	47.8
Max. temperaturno območje [°C]	50
A [mm]	63.0
B [mm]	210.8
Pretok [l/min]	450