

Datum: 06.05.2025



(slika je simbolična)

## Mikrometrski manometer, priklop spodaj, G 1/2, 0 - 4 bar, Ø 160

Kategorija: [Precision pressure gauges](#)

Šifra: **102568RIE**

### Kratek opis

Micrometre pressure gauge, Connection radial bottom, G 1/2, Goods class 0.6, Measurement range 0-4 bar, Ø 160 Bourdon-tube pressure gauge for precision measurements. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

|                                            |                       |
|--------------------------------------------|-----------------------|
| Min. sobna temperatura [°C]                | -20                   |
| Min. temperatura medija [°C]               | -20                   |
| Material Prozessanschluss                  | Copper alloy          |
| Merilni element                            | Copper alloy          |
| Ohišje                                     | CrNi steel            |
| Okvir                                      | CrNi steel            |
| Položaj povezave                           | radial on bottom      |
| Povezava                                   | G 1/2                 |
| Prednje steklo                             | Flat instrument glass |
| Premikanje                                 | Copper alloy          |
| Spodnja/Zgornja meja območja               | Positive pressure     |
| Stopnja rasti na območju skale - bar [bar] | 0.02                  |
| Razred točnosti                            | 0.6                   |
| Merilno območje max. bar                   | 4                     |
| Max. sobna temperatura [°C]                | 60                    |
| Max. temperatura medija [°C]               | 80                    |
| Premier [mm]                               | 160                   |
| Vrsta                                      | 312.20                |