

Datum: 01.05.2025



(slika je simbolična)

## Mini izpu.vent., 1.4305, G 1/8, vkl. prit. 30 - 60 bar

Kategorija: [Stainless steel blow-off safety valve, G 1/8](#)

Šifra: **103921RIE**

### Kratek opis

Mini bleeder valve, Stainless steel, not component checked,  
Operating temp. -20 °C to 180 °C, G 1/8, Trigger pressure  
30 - 60 bar

Manual adjustment of the blow-off pressure (lock nut).

For compressed air and non-toxic, non-flammable gases,  
cannot be used for liquids due to free blow-off, not suitable  
for steam.

### Tehnične Specifikacije

|                                |                 |
|--------------------------------|-----------------|
| Min. delovna temperatura [°C]  | -20             |
| Material                       | Stainless steel |
|                                | 1.4305          |
| Navoj                          | G 1/8           |
| Tesnilo                        | FKM             |
| Vzmet                          | Stainless steel |
|                                | 1.4310          |
| Min. obratovalni tlak [bar]    | 0.5             |
| narediti [mm]                  | 3.0             |
| D [mm]                         | 7.0             |
| a/f [mm]                       | 16              |
| C [mm]                         | 27.0            |
| Min. nastavljeni tlak [bar]    | 30              |
| Max. nastavljeni tlak [bar]    | 60              |
| Max. obratovalni tlak [bar]    | 60              |
| Max. delovna temperatura [°C]  | 180             |
| Hitrost izpiranja max. [l/min] | 3000            |