

Datum: 30.04.2025



(slika je simbolična)

## Mini izpus.ventil, med., G 1/8, vkl. prit. 30 - 60 bar

Kategorija: [Blow-off safety valve G 1/8](#)

Šifra: **103907RIE**

### Kratek opis

Mini bleeder valve, Brass, not component checked,  
Operating temp. -20°C to 180°C, PN 0.5-60 bar, G 1/8,  
Trigger pressure 30-60 bar  
Manual adjustment of the blow-off pressure (lock nut).  
For compressed air and non-toxic, non-flammable gases,  
cannot be used for liquids due to free blow-off, not suitable  
for steam.

### Tehnične Specifikacije

|                                |       |
|--------------------------------|-------|
| Min. delovna temperatura [°C]  | -20   |
| Navoj                          | G 1/8 |
| Tesnilo                        | FKM   |
| Min. obratovalni tlak [bar]    | 0.5   |
| narediti [mm]                  | 3.0   |
| D [mm]                         | 7.0   |
| a/f [mm]                       | 16    |
| C [mm]                         | 27.0  |
| Min. nastavljeni tlak [bar]    | 30    |
| Max. nastavljeni tlak [bar]    | 60    |
| Max. obratovalni tlak [bar]    | 60    |
| Max. delovna temperatura [°C]  | 180   |
| Hitrost izpiranja max. [l/min] | 3000  |