

Datum: 10.05.2025



(slika je simbolična)

## Naoljevalnik »G«PC zbir.Zašč. kletkaVel. 300G 1/4

Kategorija: [Oil-mist lubricator with PC bowl, bowl guard](#)

Šifra: **116441RIE**

### Kratek opis

Mist oiler »G«, PC container, Protective cage, Mounting bracket, Size 300, G 1/4, Input pres. max. 10 bar, Working pres. 0.5-9 bar  
Proportional lubricators, oil can be filled under pressure.

### Tehnične Specifikacije

|                                 |                                                                            |
|---------------------------------|----------------------------------------------------------------------------|
| Merjenje pretoka                | At $P_1 = 8$ bar, $P_2 = 6$ bar<br>and pressure drop $\Delta_p =$<br>1 bar |
| Navoj                           | G 1/4                                                                      |
| Ohišje                          | Die-cast aluminium                                                         |
| Posoda                          | Polycarbonate container<br>with protective cage                            |
| Serija                          | G                                                                          |
| Tesnilo                         | NBR                                                                        |
| Vidna kupola                    | Brass/POM                                                                  |
| Vzmet pokrova motorja           | POM                                                                        |
| Min. delovni tlak [bar]         | 0.5                                                                        |
| Max. delovni tlak [bar]         | 9                                                                          |
| Max. vhodni tlak [bar]          | 10                                                                         |
| C [mm]                          | 44.0                                                                       |
| A [mm]                          | 51.0                                                                       |
| Max. sobna temperatura<br>[°C]  | 70                                                                         |
| Max. temperatura medija<br>[°C] | 70                                                                         |
| D [mm]                          | 125.0                                                                      |
| B [mm]                          | 169.0                                                                      |
| Velikost                        | 300                                                                        |
| Pretok [l/min]                  | 2200                                                                       |