

Datum: 10.05.2025



(slika je simbolična)

Naoljevalnik »G«PC zbir.Zašč. kletkaVel. 400G 1/2

Kategorija: [Oil-mist lubricator with PC bowl, bowl guard](#)

Šifra: **116449RIE**

Kratek opis

Mist oiler »G«, PC container, Protective cage, Mounting bracket, Size 400, G 1/2, Input pres. max. 10 bar, Working pres. 0.5-9 bar
Proportional lubricators, oil can be filled under pressure.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p =$ 1 bar
Navoj	G 1/2
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serija	G
Tesnilo	NBR
Vidna kupola	Brass/POM
Vzmet pokrova motorja	POM
Min. delovni tlak [bar]	0.5
Max. delovni tlak [bar]	9
Max. vhodni tlak [bar]	10
C [mm]	48.0
A [mm]	68.0
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
D [mm]	142.0
B [mm]	190.0
Velikost	400
Pretok [l/min]	7500