

Datum: 30.04.2025



(slika je simbolična)

## **Naoljevalnik »Stinard«PC zbir.Zašč. kletkaVel.2,G 3/8**

Kategorija: [Oil-mist lubricator with PC bowl and bowl guard](#)

Šifra: **101024RIE**

### Kratek opis

Mist oiler »Standard«, PC container, protective cage, Size 2, G 3/8, Input pressure max. 16 bar, Medium / ambient temp. max. 60 °C

Proportional lubricators, oil can be filled under pressure.

### Tehnične Specifikacije

|                              |                                                       |
|------------------------------|-------------------------------------------------------|
| Merjenje pretoka             | At $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 3/8                                                 |
| Ohišje                       | Die-cast zinc, painted silver                         |
| Posoda                       | Polycarbonate container with protective cage          |
| Razred olja                  | CL 32 acc. to DIN 51517-ISO VG 32                     |
| Serijska                     | Standard                                              |
| Tesnilo                      | NBR                                                   |
| Vidna kupola                 | PA                                                    |
| Velikost                     | 2                                                     |
| DN                           | 10                                                    |
| Max. vhodni tlak [bar]       | 16                                                    |
| C [mm]                       | 51.0                                                  |
| Max. sobna temperatura [°C]  | 60                                                    |
| Max. temperatura medija [°C] | 60                                                    |
| A [mm]                       | 70.0                                                  |
| D [mm]                       | 129.5                                                 |
| Pretok [l/min]               | 2400                                                  |