

Datum: 30.04.2025



(slika je simbolična)

Nastavljivi dušilni ventil, z izpustom (C) hitri priklop

Kategorija: [Unidirectional flow control valve](#)Šifra: **106949RIE**

Kratek opis

Throttle check valve, Discharge throttle (C) quick connector
Hose 5/3, M5, PN max. 10 bar, Temperature -20 °C to 80 °C
For throttling flow rates and regulating the piston speed of cylinders. Small dimensions, ideal for tight spaces. To be screwed directly into the valve or cylinder. The set flow rate can be locked via the lock nut in the version with knurled screw. The variants in banjo bolt construction can be rotated during assembly and are fixed after tightening. The variants with plug-in connector, rotated can also be rotated freely after assembly. The seals and lubricants used are silicone-free.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Design	Banjo bolt construction
Ffunkcija	Discharge throttle (C)
Navoj	M5
Silicone-free	Yes
Telo	Nickel-plated brass
Tesnilo	NBR
Vrsta povezave	Quick lock screw fitting
Zarobljena tesnila	Polyamide, glass fibre-reinforced (only parts in banjo bolt construction)
Za cevi [mm]	5 / 3
a/f [mm]	8
Max. obratovalni tlak [bar]	10
C [mm]	19.0
B [mm]	38.9
Max. temperaturno območje [°C]	80