

Datum: 02.05.2025

Davčna št.: SI 56119488

Telefon: 01 500 14 42

E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)

WWW: [www.mail.karchertest.staging.digitalist.si](http://www.mail.karchertest.staging.digitalist.si)



(slika je simbolična)

## Nav. priklj. 331, N.N./Z.N.Rp/R 1NBR tes.,č. kovanlit. ž.

Kategorija: [Union 331, flat seat, female/male, with NBR-seal](#)

Šifra: **113174RIE**

## Kratek opis

Fitting 331, flat sealing, IT/ET, Rp/R 1, NBR seal, Operating temp. -20°C to 200°C, black malleable cast iron, Hot-dip galva.

Maximum temperature and maximum operating pressure should not occur at the same time!

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for pipe construction.

These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.

They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

## Tehnične Specifikacije

|                                |                                                     |
|--------------------------------|-----------------------------------------------------|
| Min. temperaturno območje [°C] | -20                                                 |
| Material                       | Black malleable iron<br>B350-10, design<br>symbol A |
| Navoj                          | Rp/R 1                                              |
| Površina                       | Hot dip galvanised                                  |
| Standardni navoj               | acc. ISO 7-1                                        |
| Max. temperaturno območje [°C] | 200                                                 |