

Datum: 30.04.2025



## [Nihajne varnostne sklopke I.D. 5.5, ARO 210, „Fi cevi I.D. 8](#)

(slika je simbolična)

Kategorija: [Swing safety coupling DN 5.5, with hose stem](#)Šifra: **141608RIE**

### Kratek opis

Swing safety coupling I.D. 5.5, ARO 210, Steel, Sleeve I.D. 8,  
Operating pressure max. 25 bar, Temp. -20 °C to 100 °C  
"

Swing safety coupling with free passage.

The plug-in nipple is inserted into the coupling body and rotated by an approx. 90° motion to make the connection. As soon as the "red ring" clicks into the intended slot then a secure connection has been made. To release the connection again, the "red ring" must be pulled out and the plug-in nipple is swivelled to the stopper into the starting position. Venting is done during uncoupling through a vent hole on the back side of the coupling.

This coupling meets ISO standard DIN EN ISO 4414, EN 983.  
Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive.  
"

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Delovni tlak	max. 25 bar / max. 16 bar when attaching / detaching
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Navojni kos	Galvanised steel
Ohišje	Steel, QPQ treated
Povezava	I.D. 8
Rokav	Die-cast zinc, nickel-plated, red rubber coated
Srednje Tesnilo	Compressed air, gases NBR
Vtični profil	acc. ARO 210
DN	5.5
a/f [mm]	19
Dolžina [mm]	68.0
Max. temperaturno območje [°C]	100
Pretok	820 l/min (air)