

Datum: 05.05.2025



(slika je simbolična)

Okrogli cilinder, delujoč v dveh smereh, bat Ø 32, hod 125, G 1/8

Kategorija: [Round cylinders, double acting, with magnet](#)

Šifra: **105851RIE**

Kratek opis

Round cylinder, double-acting, with magnet, Piston Ø 32, Stroke 125, G 1/8, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

Version with magnetic piston.

Suitable for filtered (50 µm), unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Technopolymer
Batnica	C45 steel, hard chrome-plated
Cushioning	non-cushioned
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Navoj na batnici	M10x1.25
Oblika	Screwed joint between stainless steel barrel and heads
Ovoj	Anodised aluminium
Povezava	G 1/8
Tesnilo	NBR
Min. nastavljeni tlak [bar]	0.4
Max. delovni tlak [bar]	10
Bat Ø [mm]	32
Max. temperaturno območje [°C]	80
Stroke [mm]	125