

Datum: 11.05.2025



(slika je simbolična)

Okrogli cilinder, enosmerni, bat Ø 16, hod 25, M5

Kategorija: [Round cylinders, single-acting, with magnet](#)

Šifra: **105832RIE**

Kratek opis

Round cylinder, ISO 6432, single-acting, Magnet, Piston Ø 16, Stroke 25, M5, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

Single and double-acting cylinders, with magnetic piston. Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Synthetic (acetal) resin
Batnica	C45 steel, hard chrome-plated
Cushioning	non-cushioned
Ffunkcija	single-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Navoj na batnici	M6
Oblika	Flanged joint between stainless steel barrel and heads
Ovoj	Stainless steel 1.4301
Povezava	M5
Standard	acc. to ISO 6432
Starting position	pressureless in the retracted position
Tesnilo	NBR
Min. nastavljeni tlak [bar]	0.6
Max. delovni tlak [bar]	10
Bat Ø [mm]	16
Stroke [mm]	25
Max. temperaturno območje [°C]	80