

Datum: 01.05.2025



(slika je simbolična)

## Okrogli cilinder »MSI« enosmerni, bat Ø 8, hod 40, M5x0.8

Kategorija: [Round cylinder, single-acting, with magnet, CA](#)

Šifra: **114932RIE**

### Kratek opis

Round cylinder »MSI«, single-acting, Magnet, Piston Ø 8, Stroke 40, M5x0.8, Working pressure 2 - 10 bar, Temp. -20 °C to 70 °C

These round cylinders are available in the following versions:

- »MI« Series, double-acting, Ø 8 to 25 acc. to ISO 6432
- »MI« Series, double-acting, Ø 32 to 40
- »MSI« Series, single-acting, pressureless in the retracted position, Ø 32 to 40

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

»CA« type = bottom cover with male thread - hinge

model? »CM« type = bottom cover with male thread, round - hinge model

### Tehnične Specifikacije

|                                |                                        |
|--------------------------------|----------------------------------------|
| Min. temperaturno območje [°C] | -20                                    |
| Bat                            | Stainless steel 1.4305                 |
| Batnica                        | Stainless steel 1.4301                 |
| Cushioning                     | non-cushioned                          |
| ET batnice                     | M4x0.7                                 |
| Ffunkcija                      | single-acting                          |
| Gewinde Kolbenstange           | male piston rod                        |
| Magnet                         | with magnet                            |
| Ovoj                           | Stainless steel 1.4301                 |
| Povezava                       | M5x0.8                                 |
| Serijska                       | MSI series                             |
| Starting position              | pressureless in the retracted position |
| Tesnilo                        | NBR                                    |
| Vrsta                          | CA type                                |
| Min. delovni tlak [bar]        | 2                                      |
| Batnica Ø [mm]                 | 4                                      |
| Bat Ø [mm]                     | 8                                      |
| Max. delovni tlak [bar]        | 10                                     |
| Stroke [mm]                    | 40                                     |
| Max. temperaturno območje [°C] | 70                                     |