

Datum: 10.05.2025



(slika je simbolična)

Okrogli cilinder »MSI« enosmerni, batØ 16, hod 30, M5x0.8

Kategorija: [Round cylinder, single-acting, with magnet, CA](#)Šifra: **114952RIE**

Kratek opis

Round cylinder »MSI«, single-acting, Magnet, Piston Ø 16, Stroke 30, M5x0.8, Working pressure 2 - 10 bar, Temp. -20 °C to 70 °C

These round cylinders are available in the following versions:

- »MI« Series, double-acting, Ø 8 to 25 acc. to ISO 6432
- »MI« Series, double-acting, Ø 32 to 40
- »MSI« Series, single-acting, pressureless in the retracted position, Ø 32 to 40

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

»CA« type = bottom cover with male thread - hinge

model?»CM« type = bottom cover with male thread, round - hinge model

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Stainless steel 1.4301
Cushioning	non-cushioned
ET batnice	M6x1.0
Ffunkcija	single-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Stainless steel 1.4301
Povezava	M5x0.8
Serijska	MSI series
Starting position	pressureless in the retracted position
Tesnilo	NBR
Vrsta	CA type
Min. delovni tlak [bar]	2
Batnica Ø [mm]	6
Max. delovni tlak [bar]	10
Bat Ø [mm]	16
Stroke [mm]	30
Max. temperaturno območje [°C]	70