

Datum: 08.05.2025



(slika je simbolična)

Osn.ejektor SBP-C, izpust. vent., z dušilko, velikost šobe 2 mm

Kategorija: [Basic ejector SBP-C blow-off valve el. vac. switch](#)

Šifra: **108395RIE**

Kratek opis

Basic ejector »SBP-C«, Bleeder valve elec. vacuum switch, Silencer, Nozzle size 2 mm, Compressed air / vacuum connection 8/10 mm

Purely pneumatic vacuum generator that operates on the Venturi principle.

Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

Properties:

- Vacuum generator with a single nozzle, available in six power ratings, with a high maximum vacuum value (85%)
- Connection of compressed air and vacuum with push-in coupling
- Basic housing with connection facility for a vacuum switch
- Maximum suction capacity with minimum compressed air consumption

• Minimum size, low weight

• Various power ratings for optimised air consumption

Applications:

- For universal use in handling systems with very high dynamic movements
- Handling all kinds of air-tight components
- For use in separation systems where space is restricted
- Construction of ejector blocks for centralised or decentralised individual control of suction pads

Tehnične Specifikacije

Dušilec	Plastic
Položaj sesalnega ventila v mirovanju	NO
Povezava	Push-in coupling
Sistem šobe	Brass
Telo	Plastic (impact-resistant)
Velikost šobe [mm]	2
Dovod stisnjenega zraka	8 mm
Dovod vakuumu	10 mm
Premier [mm]	20.0
Višina [mm]	72.0
Dolžina [mm]	228.0