

Datum: 30.04.2025



(slika je simbolična)

## Plošč.ventil HDM prik.6mm 2x3/2 NO mono ali 5/3 sredina odzračena

Kategorija: [Valve disc for HDM valve terminal with 6 mm port](#)

Šifra: **106682RIE**

### Kratek opis

Valve disc for valve terminal HDM, Connection 6 mm, 2x 3/2-way, NC, monostable or 5/3-way, Centre vented  
These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates.  
Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.  
Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.  
Monostable (non-latching) version of manual control also available on request.  
The operating pressure is based on the installed input plates.

### Tehnične Specifikacije

|                                |                                                                                |
|--------------------------------|--------------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                                            |
| IP zaščita                     | IP 65                                                                          |
| Material                       | aluminium                                                                      |
| Poskusno                       | Max. 16 (e.g. 16 spring return valves)                                         |
| Ročno upravljanje              | latching                                                                       |
| Vhodna moč                     | 0.6 W per pilot<br>2x 3/2-way, NO,<br>monostable or 5/3-way,<br>centre aerated |
| Ffunkcija                      |                                                                                |
| Max. temperaturno območje [°C] | 60                                                                             |
| Pretok [NI/min]                | 500                                                                            |