

Datum: 30.04.2025



(slika je simbolična)

Ploščati ventil HDM priključek 8 mm 5/3-potni, sredina zaprta

Kategorija: [Valve disc for HDM valve terminal with 8 mm port](#)

Šifra: **106694RIE**

Kratek opis

Valve disc for valve terminal HDM, Connection 8 mm, 5/3-way, Centre closed, Temp. -10 °C to 60 °C

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates.

Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Monostable (non-latching) version of manual control also available on request.

The operating pressure is based on the installed input plates.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
IP zaščita	IP 65
Material	aluminium
Poskusno	Max. 16 (e.g. 16 spring return valves)
Ročno upravljanje	latching
Vhodna moč	0.6 W per pilot
Ffunkcija	5/3-way, centre closed
Max. temperaturno območje [°C]	60
Pretok [NI/min]	800