

Datum: 07.05.2025



(slika je simbolična)

Pnevmatski zapotni ventil, G 3/8, G 3/8 i., G 1/8

Kategorija: [Pneumatically piloted stop valves](#)

Šifra: **107059RIE**

Kratek opis

Pneumatically piloted stop valve, G 3/8, G 3/8 i., G 1/8,
Working pressure 0.3-10 bar, Temperature -10°C to 60°C
For stopping and positioning the cylinder movement:
If a control signal is present at port 3 (see drawing), air can
flow to and from the cylinder. If no control signal is present,
the cylinder exhaust air is shut off by the unidirectional
valve. The cylinder is stopped. Releasable unidirectional
valves are screwed directly onto the cylinder instead of the
normal pipe connections.
Note: Pilot pressure is depending on operating pressure.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Material	Nickel-plated brass
Port 1	G 3/8
Port 2	G 3/8
Port 3	G 1/8
Tesnilo	NBR
Vgradni položaj	Any, ring piece must be pos. before tightening the valve
Min. obratovalni tlak [bar]	0.3
Min. vodeni tlak [bar]	0.5
Max. vodeni tlak [bar]	2.5
Max. obratovalni tlak [bar]	10
C [mm]	31.6
B [mm]	46.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60