

Datum: 30.04.2025



(slika je simbolična)

Polnilna enota »FUTURA«, pnevmatsko vodena, Velikost 1, G 3/8

Kategorija: [Filling units, pneumatically operated](#)

Šifra: **156633RIE**

Kratek opis

Filling unit »FUTURA«, pneumatically actuated, Size 1, G 3/8, Exhaust G 1/4, Input pressure 2.5 - 16 bar, Temp. -10 °C to 50 °C

The filling unit protects devices connected downstream by ensuring a gradual build-up of pressure.

The unit consists of a 3/2-way valve including silencer and a filling valve (start-up valve).

It is connected and disconnected by means of the 3/2-way valve.

The filling time can be altered by turning the adjusting screw.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Izpušni zrak	G 1/4 At $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Merjenje pretoka	
Navoj	G 3/8
Ohišje	PA66 GF60
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Velikost	1
Min. vhodni tlak [bar]	2.5
Max. vhodni tlak [bar]	16
D [mm]	33.0
Max. temperaturno območje [°C]	50
C [mm]	52.1
B [mm]	85.1
A [mm]	104.0
Pretok [l/min]	1400