

**Datum:** 23.05.2025**TRG d.o.o.**  
**Celovška cesta 150, 1000 Ljubljana****Davčna št.:** SI 56119488  
**Telefon:** 01 500 14 42  
**E-mail:** [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
**WWW:** [www.mail.karchertest.staging.digitalist.si](http://www.mail.karchertest.staging.digitalist.si)

## Polyurethane hose, Hose Ø 3x0.75 mm, blue, Roll of 25 m

(slika je simbolična)

Kategorija: [Polyurethane hose \(PUR\)](#)Šifra: **113647RIE**

### Kratek opis

Polyurethane hose (PUR), Temperature -20 °C to 60 °C, Hose Ø 3x0.75 mm, PN at 23 °C max. 13 bar, blue, Roll of 25 m

Polyurethane hoses are renowned for their extreme flexibility and correspondingly narrow bending radius across a wide temperature range.

They are more flexible even than LD-PE hoses and exhibit good abrasion resistance, very good low-temperature flexibility, only minimal permanent deformation when subjected to long-term stresses as well as good resistance to the majority of oils, greases, aliphatic hydrocarbons and oxygen.

Main applications:

- Pneumatic and hydraulic (miniature hydraulics) lines
- Mechanical engineering
- Engine construction
- Instrumentation and control
- Ideal for use with unions, as externally calibrated

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Barva	Blue
Material	Polyurethane (PUR)
Debelina stene [mm]	0.75
I.D. cevi [mm]	1.5
O.D. cevi [mm]	3
Max. obratovalni tlak pri 23 ° C [bar]	13
Dolžina koluta [m]	25
Max. temperaturno območje [°C]	60