

Datum: 01.05.2025



(slika je simbolična)

Pravokotni krogelni ventil, nikljana medenina, ET/ET, R 1/2

Kategorija: [Ball valve, angle type, male/male thread](#)

Šifra: **103316RIE**

Kratek opis

Rectangular ball valve, nickel-plated brass, ET/ET, Operating temp. -15 °C to 100 °C/60 °C gas, R 1/2, PN max. 40 bar/ 5 bar gas

Tehnične Specifikacije

Delovna temperatura	-15 °C to 60 °C for gas, -15 °C to 100 °C for liquids
Aplikacije	Gas, compressed air, water, oil
Delovni tlak	max. 5 bar (MOP 5) gas, max. 40 bar liquids
DVGW odobritev	DIN EN 331:2013-05
Krogelno tesnilo	PTFE
Material navojev	Brass with a bare metal surface
Navoj	R 1/2
Notranji deli	Nickel-plated brass
Ohišje	Nickel-plated brass
Ročica - metuljček	Aluminium, painted yellow
Standardni navoj	R thread acc. to ISO 7-1
Stebelno tesnilo	NBR
DN	15
C Ø [mm]	31.0
F [mm]	35.0
E [mm]	37.0
B [mm]	38.0
A [mm]	47.0