

Datum: 30.04.2025



(slika je simbolična)

Predfilter»FUTURA«Kov. pos.0.3 µm, Vel. 4, G 1, Avt.

Kategorija: [Pre-filter with metal bowl and sight glass](#)

Šifra: **156571RIE**

Kratek opis

Pre-filter »FUTURA« with metal container and viewing tube, 0.3 µm, Size 4, G 1, 1.5 - 16 bar, Temp. -10°C to 50°C, Fully-automatic

Pre-filters in modern design for compliance with strict compressed air purity requirements.

Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Impregnated paper
Merjenje pretoka	At P ₂ = 6 bar and pressure drop Δ _p = 0.02 bar
Navoj	G 1
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Rang filtra [µm]	0.3
Min. vhodni tlak [bar]	1.5
Velikost	4
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	63.0
A [mm]	85.0
B [mm]	269.0
Pretok [l/min]	1500