

Datum: 30.04.2025



(slika je simbolična)

Predfilter»FUTURA« Kov. pos.0.3 µm, Vel.1, G 3/8, Avt.

Kategorija: [Pre-filter with metal bowl and sight glass](#)

Šifra: **156567RIE**

Kratek opis

Pre-filter »FUTURA« with metal container and viewing tube, 0.3 µm, Size 1, G 3/8, 1.5-16 bar, Temp. -10°C to 50°C, Fully-automatic
Pre-filters in modern design for compliance with strict compressed air purity requirements.
Pre-filters are used to separate solid impurities up to 0.3 µm from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Impregnated paper
Merjenje pretoka	At P ₂ = 6 bar and pressure drop Δ _p = 0.02 bar
Navoj	G 3/8
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Rang filtra [µm]	0.3
Velikost	1
Min. vhodni tlak [bar]	1.5
Max. vhodni tlak [bar]	16
C [mm]	39.5
Max. temperaturno območje [°C]	50
A [mm]	52.0
B [mm]	186.5
Pretok [l/min]	300