

Datum: 30.04.2025



(slika je simbolična)

## Predfiltrirajte brez diferencialnega tlaka, 3 µm, G 3/8

Kategorija: [Pre-filter without differential pressure gauge](#)

Šifra: **101553RIE**

### Kratek opis

Pre-filter without differential pressure gauge, 3 µm, G 3/8,  
Input pressure 4 - 12 bar, Medium / ambient temperature 5  
°C to 60 °C

For filtering out solid impurities larger than 3 µm and for  
moisture separation.

For connection upstream of a micro-filter or a combination  
micro-filter/activated carbon filter.

### Tehnične Specifikacije

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| Element filtra               | Borosilicate<br>microfibre fabric                                       |
| Ločevanje delcev [µm]        | from 3                                                                  |
| Merjenje pretoka             | At P <sub>1</sub> = 6 bar and<br>pressure drop Δ <sub>p</sub> =<br>0.5% |
| Navoj                        | G 3/8                                                                   |
| Ohišje                       | Aluminium                                                               |
| Posoda filtra                | Aluminium                                                               |
| Rang filtra [µm]             | 3                                                                       |
| Min. vhodni tlak [bar]       | 4                                                                       |
| Min. sobna temperatura [°C]  | 5                                                                       |
| Min. temperatura medija [°C] | 5                                                                       |
| Max. vhodni tlak [bar]       | 12                                                                      |
| C [mm]                       | 57.0                                                                    |
| Max. sobna temperatura [°C]  | 60                                                                      |
| Max. temperatura medija [°C] | 60                                                                      |
| A [mm]                       | 83.0                                                                    |
| Učinkovitost [%]             | 99.99                                                                   |
| B2 [mm]                      | 335.0                                                                   |
| D [mm]                       | 353.0                                                                   |
| Pretok [l/min]               | 1000                                                                    |